



series

STANDARD VERSION



W70 - W71 - W91

Standard version with nickel plated aluminium head.
Version with brass head available on request.

Version standard avec culasse en aluminium nickelé.
Version avec culasse laiton disponible sur requête.

Standardausführung mit vernickeltem Aluminiumkopf.
Ausführung mit Messingkopf lieferbar auf Wunsch.

Versión standard con culata de aluminio niquelado.
Versión con culata de latón disponible bajo pedido.

Versione standard con testata in alluminio nichelato.
Disponibile su richiesta la versione con testata in ottone.

Pump type Type de pompe Pumpentype Tipo de bomba Tipo di pompa	Flow rate Débit Förderleistung Caudal Portata l/min.	G.P.M. (U.S.A.)	Max. pressure Pression Druck Presión Pressione bar	MPa	p.s.i.	r.p.m. tr./min. u.p.m. r/min. g./min.	Power Puissance Leistung Potencia Potenza kW	hp	Weight Poids Gewicht Peso Peso kg	Inlet Entrée Eingang Entrada Entrata	Outlet Sortie Ausgang Salida Uscita	Dimensions Dimensions Dimension Dimensiones Dimensioni mm
W70	11	2.9	70	7	1015	1450	1,47	2	6,5	G 1/2 F	G 3/8 F	238x211x138
W98	11	2.9	100	10	1450		2,20	3	8,5	G 1/2 F	G 3/8 F	
WS149	11	2.9	140	14	2030		2,94	4	8,7	G 1/2 F	G 3/8 F	
W71	13	3.43	70	7	1015		1,83	2,5	6,5	G 1/2 F	G 3/8 F	
W91	13	3.43	90	9	1300		2,20	3	6,5	G 1/2 F	G 3/8 F	
W99	13	3.43	100	10	1450		2,42	3,3	8,5	G 1/2 F	G 3/8 F	
WS137	13	3.43	120	12	1750	1750	2,94	4	8,7	G 1/2 F	G 3/8 F	238x211x138
W995	13	3.43	90	9	1300		2,20	3	8,5	G 1/2 F	G 3/8 F	
W996	15	3.96	75	7,5	1100		2,20	3	8,5	G 1/2 F	G 3/8 F	
W997	15	3.96	140	14	2030		4,04	5,5	8,7	G 1/2 F	G 3/8 F	

50 series



Pump type Type de pompe Pumpentype Tipo de bomba Tipo di pompa	Flow rate Débit Förderleistung Caudal Portata	G.P.M. (U.S.A.)	Max. pressure Pression Druck Presión Pressione	r.p.m. tr./min. u.p.m. r/min. g./min.	Power Puissance Leistung Potencia Potenza	Weight Poids Gewicht Peso Peso	Inlet Entrée Eingang Entrada Entrata	Outlet Sortie Ausgang Salida Uscita	Dimensions Dimensions Dimension Dimensiones Dimensioni
	l/min.		bar MPa p.s.i.		kW hp	kg			mm
WW141	11,5	3.04	140 14 2030	2800	2,94 4	8,5	G 1/2 F	G 3/8 F	238x211x138
WW161	14	3.69	160 16 2320		4,04 5,5		G 1/2 F	G 3/8 F	
WW935	13,2	3.48	172 17,2 2500	3400	4,41 6	8,5	G 1/2 F	G 3/8 F	238x211x138
WW944	16,6	4.38	172 17,2 2500		5,51 7,5		G 1/2 F	G 3/8 F	